SAFETY DATA SHEET



1. Product and Company Identification

Product Name: Reynco 55-892 Adhesive

The Reynolds Company Emergency Phone Number (24 hours/day)

P.O. Box 1925 Chemtrec: 800-424-9300 Greenville, SC 29602

For additional health, safety, or regulatory

information, call 864-232-6791 during business hours.

Product Use: Product Assembly Adhesive

Not recommended for:

2. Occupational Health and Safety Components

GHS Ratings:

GHS Hazards

H335 GHS Precautions	May cause respiratory irritation		
P103	Read label before use		
P264	Wash thoroughly after handling		
P281	Use personal protective equipment as required		
P302	IF MOLTEN MATERIAL ON SKIN: Immediately immerse in or flush with large amounts of of cool water to dissipate heat. Do not try to remove adhesive.		
P304	Cover with clean cotton and get prompt medical attention IF INHALED:		
P308	IF exposed or concerned:		
P313	Get medical advice/attention		
P332	If skin irritation occurs:		
P334	Immerse in cool water/wrap in wet bandages		
P341	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing		
P362	Take off contaminated clothing and wash before reuse		
P302+P352	IF ON SKIN: Wash with soap and water		
P308+P313	IF exposed or concerned: Get medical advice/attention		
P332+P313	If skin irritation occurs: Get medical advice/attention		
P405	Store locked up		
P501	Dispose of contents/container to approved waste disposal plant.		

Signal Word:

Acute Toxicity: None

Conditions Aggravated: Hot fumes may cause eye, skin or respiratory irritations

Chronic Effects: None known.

3. Hazards Identification

*Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) See Section 8 for exposure limit guidelines.

* Ingredient Disclosure List (IDL). All ingredients in this product are listed on the Domestic Substance List (DSL).

4. First Aid Measures

Inhalation: Not likely. Move victim to fresh air if needed.

Eye Contact: For material in supplied state - immediately flush eyes with plenty of water for at least 15 minutes- occasionally lift eyelids. Call a physician if irritation persists.

Skin Contact: For contact with material as supplied- wash with soap and and water. For molten adhesive - immediately immerse in or flush with large amounts of cold water to dissipate heat. Cover with clean cotton and get prompt medical attention.

Ingestion: Not likely in normal use. If swallowed, do not induce vomiting. Give 2 glasses of water (16oz.) and contact a physician.

Notes to Physician: Product in original form should pose no hazard. Material is heated to apply. Molten material may cause burns.

5. Firefighting Measures

Flash Point: Not determined

LEL: UEL:

Flammable Limits: Not established

Extinguishing Media: Water spray of fog, CO2, or dry chemical. Use care not to splash adhesive.

Unusual Fire and Explosion Hazards: Material will burn in a fire.

Hazardous Combustion Products: None hazardous. Carbon dioxide, carbon monoxide and various

hydrocarbons.

Firefighting:: Wear self-contained breathing apparatus.

Fire Equipment: Wear self-contained breathing apparatus. Keep containers cool to prevent rupture.

6. Accidental Release Procedures

Spillage: Ensure that all clean-up personnel wear all appropriate protective equipment. Do not allow material to get into sewer or waterway.

Small Spills: Sweep or vacuum materials. Dispose in trash.

Large Spills: Sweep or vacuum materials. Dispose of as non hazardous waste.

7. Handling and Storage

Handling: Routine housekeeping should be in place to assure that material does not accumulate on surfaces. Clean up small spills.

Storage Requirements: Normal storage temperatures in a dry warehouse.

Regulatory Requirements: During hot processing air removal or air flow may be necessary.

8. Exposure Control and Personal Protection

Chemical Name / CAS No. OSHA Exposure Limits ACGIH Exposure Limits Other Exposure Limits

SDS for: Revnco 55-892 Adhesive

Page 2 of 5
Printed: 4/18/2017 at 8:36:27AM

Distillates, petroleum,	Not Established	Not Established	Not Established
hydrotreated heavy naphthenic			
64742-52-5			

Engineering Controls: Ventilation should be sufficient to control airborne levels/fumes.

Ventilation: Use in a properly ventilated area.

Administrative Controls: Use good personal hygiene when handing this product. Wash hands after use,

before smoking, eating, or using the toilet.

Protective Gear: Wear safety glasses near extrusion and fill points. Wear heat resistant gloves when

working near molten material.

Contaminated Gear: Use care if molten material is on gear. Do not try to remove until it has cooled.

9. Physical and Chemical Properties

Properties are supplied for safety, health and environmental considerations and may not fully represent product specifications.

Vapor Pressure: Not determined

Flash point: Not determined

Flammability: Not determined

Appearance: Yellow to Amber

solid

Vapor Density: Not applicagle

Specific Gravity Not determined

Freezing point: Not appleable

Boiling range: Not determined

Autoignition temperature: Not determined

Viscosity 4,000-9,000

cps@350F

Odor threshold: Not determined

Evaporation rate: Not determined

Explosive Limits: Not determined

Odor: Resinous

pH: Not applicable

Mettler Drop Point: Not determined

Solubility: Insoluble in water

Partition coefficient (n- Not determined

octanol/water):

Decomposition temperature: Not determined

EPA 24 VOC: Not determined

10. Stability and Reactivity

Stability:

STABLE

Incompatible Materials:

Hazardous Decomposition Products:

11. Toxicological Information

Mixture Toxicity

Toxicity: Information appears only if there are issues that need to be considered.

Routes of Entry: Material in furnished state does not pose any hazards.

Target Organs: Exposure to this material may affect the following organs:

SDS for: Revnco 55-892 Adhesive

Page 3 of 5

Skin: Contact with molten material can cause burns.

Eyes: Vapors from molten product might cause eye irritation.

Respiratory System: Vapors from molten product might cause nose irritation.

Effects of Overexposure

Carcinogenicity: None

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

Distillates, petroleum, hydrotreated heavy naphthenic hydrotreated heavy naphthenic

hydrotreated heavy naphthenic:

EU REACH: Present (L)

12. Ecological Information

Ecological: Any information available follows.

Component Ecotoxicity

Distillates, petroleum, 96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L hydrotreated heavy naphthenic 48 Hr EC50 Daphnia magna: >1000 mg/L

13. Disposal Considerations

Disposal: Reclaim if feasible. If disposal is required, dispose of material and waste in a sanitary landfill or incinerate in an industrial, commercial, or municipal incinerator.

14. Transport Information

Transportation Instructions:

Agency Proper Shipping Name UN Number Packing Group Hazard Class

DOT Not regulated IATA Not regulated

15. Regulatory Information

The following information is provided based upon the best information at our disposal.

<u>Country</u> <u>Regulation</u> <u>All Components Listed</u>

Toxic Substances Control Act Yes

16. Other Information


For any valid claim presented under the limited warranty, Reynolds will replace the product, or, at its option, refund the purchase price. This replacement/refund resolution is the purchaser's sole and exclusive remedy against Reynolds. The purchaser agrees that no other resolution (including but not limited to lost profits, lost sales, injury to person or property or any other incidental or consequential loss) shall be available to purchaser for claims arising out of any use of the product regardless of the legal theory (contract, tort or other). In no event will Reynolds be obligated to pay damages to purchaser in any amount exceeding the price that the purchaser paid for the product. The Reynolds Company ("Reynolds") warrants that our products are manufactured in accordance with Reynolds' specifications in effect on the date of manufacture. These specifications are available upon request. This Warranty does not cover test data, or any defects, damages or other harms caused to any extent or in any way by failure to follow applicable Reynolds instructions, if any, or abuse /misuse of the product.

Any claim made or action commenced by purchaser/end user under Reynolds' limited warranty as set forth herein must be brought within one year from date of shipment from Reynolds to the purchaser. Purchaser agrees that all disputes arising from Reynolds' sale of product to purchaser shall be brought, if at all, in and before a court located in the state of South Carolina, to the exclusion of the courts of any other

SDS for: Revnco 55-892 Adhesive

Page 4 of 5

Hazardous Material Information System (HMIS)



DISCLAIMER - The warranty, as stated above, supersedes all other warranties, express or implied. The Reynolds Company expressly disclaims any other warranties, including warranties of merchantability and fitness for a particular purpose. Reynolds Company's acceptance of purchaser's order for this product is expressly conditional on purchaser's assent to terms and conditions set forth herein. Regardless of whether The Reynolds Company suggested the product or developed the product at the purchaser's request, it is the purchaser's responsibility to test and determine the suitability of the product for the purchaser's intended use and purpose, and purchaser assumes all risk and liability whatsoever.

We believe the information included on this Material Safety Data Sheet to be correct, to the best of our knowledge. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that tests be made in a laboratory or plant to determine if this product meets all of your requirements. It is the responsibility of the buyer/user to determine the suitability of this product for his/her application/requirements.

Reviewer Revision

Date Prepared: 4/18/2017

SDS for: Revnco 55-892 Adhesive

Page 5 of 5