

SAFETY DATA SHEET



1. Product and Company Identification

Product Name: Reynco 55-892 Adhesive

The Reynolds Company
P.O. Box 1925
Greenville, SC 29602

Emergency Phone Number (24 hours/day)
Chemtrec: 800-424-9300

For additional health, safety, or regulatory information, call 864-232-6791 during business hours.

Product Use: Product Assembly Adhesive
Not recommended for:

2. Occupational Health and Safety Components

GHS Ratings:

GHS Hazards

H335 May cause respiratory irritation

GHS Precautions

P103 Read label before use
P264 Wash ... thoroughly after handling
P281 Use personal protective equipment as required
P302 IF MOLTEN MATERIAL ON SKIN: Immediately immerse in or flush with large amounts of cool water to dissipate heat. Do not try to remove adhesive. Cover with clean cotton and get prompt medical attention
P304 IF INHALED:
P308 IF exposed or concerned:
P313 Get medical advice/attention
P332 If skin irritation occurs:
P334 Immerse in cool water/wrap in wet bandages
P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P362 Take off contaminated clothing and wash before reuse
P302+P352 IF ON SKIN: Wash with soap and water
P308+P313 IF exposed or concerned: Get medical advice/attention
P332+P313 If skin irritation occurs: Get medical advice/attention
P405 Store locked up
P501 Dispose of contents/container to approved waste disposal plant.

Signal Word:

Acute Toxicity: None

Conditions Aggravated: Hot fumes may cause eye, skin or respiratory irritations

Chronic Effects: None known.

3. Hazards Identification

*Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) See Section 8 for exposure limit guidelines.

* Ingredient Disclosure List (IDL). All ingredients in this product are listed on the Domestic Substance List (DSL).

4. First Aid Measures

Inhalation: Not likely. Move victim to fresh air if needed.

Eye Contact: For material in supplied state - immediately flush eyes with plenty of water for at least 15 minutes- occasionally lift eyelids. Call a physician if irritation persists.

Skin Contact: For contact with material as supplied- wash with soap and and water. For molten adhesive - immediately immerse in or flush with large amounts of cold water to dissipate heat. Cover with clean cotton and get prompt medical attention.

Ingestion: Not likely in normal use. If swallowed, do not induce vomiting. Give 2 glasses of water (16oz.) and contact a physician.

Notes to Physician: Product in original form should pose no hazard. Material is heated to apply. Molten material may cause burns.

5. Firefighting Measures

Flash Point: Not determined

LEL:

UEL:

Flammable Limits: Not established

Extinguishing Media: Water spray of fog, CO₂, or dry chemical. Use care not to splash adhesive.

Unusual Fire and Explosion Hazards: Material will burn in a fire.

Hazardous Combustion Products: None hazardous. Carbon dioxide, carbon monoxide and various hydrocarbons.

Firefighting:: Wear self-contained breathing apparatus.

Fire Equipment: Wear self-contained breathing apparatus. Keep containers cool to prevent rupture.

6. Accidental Release Procedures

Spillage: Ensure that all clean-up personnel wear all appropriate protective equipment. Do not allow material to get into sewer or waterway.

Small Spills: Sweep or vacuum materials. Dispose in trash.

Large Spills: Sweep or vacuum materials. Dispose of as non hazardous waste.

7. Handling and Storage

Handling: Routine housekeeping should be in place to assure that material does not accumulate on surfaces. Clean up small spills.

Storage Requirements: Normal storage temperatures in a dry warehouse.

Regulatory Requirements: During hot processing air removal or air flow may be necessary.

8. Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	Not Established	Not Established	Not Established
--	-----------------	-----------------	-----------------

Engineering Controls: Ventilation should be sufficient to control airborne levels/fumes.

Ventilation: Use in a properly ventilated area.

Administrative Controls: Use good personal hygiene when handling this product. Wash hands after use, before smoking, eating, or using the toilet.

Protective Gear: Wear safety glasses near extrusion and fill points. Wear heat resistant gloves when working near molten material.

Contaminated Gear: Use care if molten material is on gear. Do not try to remove until it has cooled.

9. Physical and Chemical Properties

Properties are supplied for safety, health and environmental considerations and may not fully represent product specifications.

<p>Vapor Pressure: Not determined</p> <p>Flash point: Not determined</p> <p>Flammability: Not determined</p> <p>Appearance: Yellow to Amber solid</p> <p>Vapor Density: Not applicable</p> <p>Specific Gravity: Not determined</p> <p>Freezing point: Not applicable</p> <p>Boiling range: Not determined</p> <p>Autoignition temperature: Not determined</p> <p>Viscosity: 4,000-9,000 cps@350F</p>	<p>Odor threshold: Not determined</p> <p>Evaporation rate: Not determined</p> <p>Explosive Limits: Not determined</p> <p>Odor: Resinous</p> <p>pH: Not applicable</p> <p>Mettler Drop Point: Not determined</p> <p>Solubility: Insoluble in water</p> <p>Partition coefficient (n-octanol/water): Not determined</p> <p>Decomposition temperature: Not determined</p> <p>EPA 24 VOC: Not determined</p>
--	---

10. Stability and Reactivity

Stability:
STABLE

Incompatible Materials:

Hazardous Decomposition Products:

11. Toxicological Information

Mixture Toxicity

Toxicity: Information appears only if there are issues that need to be considered.

Routes of Entry: Material in furnished state does not pose any hazards.

Target Organs: Exposure to this material may affect the following organs:

Skin: Contact with molten material can cause burns.

Eyes: Vapors from molten product might cause eye irritation.

Respiratory System: Vapors from molten product might cause nose irritation.

Effects of Overexposure

Carcinogenicity: None

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic		Distillates, petroleum, hydrotreated heavy naphthenic: EU REACH: Present (L)

12. Ecological Information

Ecological: Any information available follows.

Component Ecotoxicity

Distillates, petroleum, hydrotreated heavy naphthenic	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L
---	--

13. Disposal Considerations

Disposal: Reclaim if feasible. If disposal is required, dispose of material and waste in a sanitary landfill or incinerate in an industrial, commercial, or municipal incinerator.

14. Transport Information

Transportation Instructions:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not regulated			
IATA	Not regulated			

15. Regulatory Information

The following information is provided based upon the best information at our disposal.

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
	Toxic Substances Control Act	Yes

16. Other Information

For any valid claim presented under the limited warranty, Reynolds will replace the product, or, at its option, refund the purchase price. This replacement/refund resolution is the purchaser's sole and exclusive remedy against Reynolds. The purchaser agrees that no other resolution (including but not limited to lost profits, lost sales, injury to person or property or any other incidental or consequential loss) shall be available to purchaser for claims arising out of any use of the product regardless of the legal theory (contract, tort or other). In no event will Reynolds be obligated to pay damages to purchaser in any amount exceeding the price that the purchaser paid for the product. The Reynolds Company ("Reynolds") warrants that our products are manufactured in accordance with Reynolds' specifications in effect on the date of manufacture. These specifications are available upon request. This Warranty does not cover test data, or any defects, damages or other harms caused to any extent or in any way by failure to follow applicable Reynolds instructions, if any, or abuse /misuse of the product.

Any claim made or action commenced by purchaser/end user under Reynolds' limited warranty as set forth herein must be brought within one year from date of shipment from Reynolds to the purchaser. Purchaser agrees that all disputes arising from Reynolds' sale of product to purchaser shall be brought, if at all, in and before a court located in the state of South Carolina, to the exclusion of the courts of any other

state.

Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

DISCLAIMER - The warranty, as stated above, supersedes all other warranties, express or implied. The Reynolds Company expressly disclaims any other warranties, including warranties of merchantability and fitness for a particular purpose. Reynolds Company's acceptance of purchaser's order for this product is expressly conditional on purchaser's assent to terms and conditions set forth herein. Regardless of whether The Reynolds Company suggested the product or developed the product at the purchaser's request, it is the purchaser's responsibility to test and determine the suitability of the product for the purchaser's intended use and purpose, and purchaser assumes all risk and liability whatsoever.

We believe the information included on this Material Safety Data Sheet to be correct, to the best of our knowledge. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that tests be made in a laboratory or plant to determine if this product meets all of your requirements. It is the responsibility of the buyer/user to determine the suitability of this product for his/her application/requirements.

Reviewer Revision

Date Prepared: 4/18/2017

QUALITY CONTROL DEPARTMENT

SPECIFICATION SHEET

The Reynolds Company
 P.O. Box 1925
 Greenville, SC. 29602
 PHONE: (864)232-6791
 FAX: (864)242-6804
 www.reynoldsglue.com

PRODUCT	
Reynco 55-892 Adhesive	5F08631527-FDH 55

SPECIFICATION	SPECIFICATION VERSION	SPECIFICATION DATE
586-55-892	2.0000	04/17/2017

PRODUCT SPECIFICATION		
TEST	TEST ID	REQUIREMENTS
Viscosity of HM in cps @350F	V350	4000 - 6100 cps
Gardner Color of HM	Gardner	<= 6 MAXIMUM

REMARKS
Pressure Sensitive Hot Melt Adhesive Specific Gravity: TDB Mettler Drop Point: 232°F Gardner Color: 6 Maximum Viscosity @325°F: 7,800-10,500cps Viscosity @350°F: 4,000- 6,100cps Viscosity @375°F: 2,800- 3,700cps

Important

The information on the sheet is believed to be accurate but is not warranted to be so. Protective equipment, health effects, and other related safety measures are based on intended and anticipated product use. Recipients are advised to confirm in advance of need that the information is applicable and suitable to their circumstances.

LIMITED WARRANTY AND TERMS

The Reynolds Company ("Reynolds") warrants that, for one year from the date of shipment from Reynolds to the original purchaser, this product was manufactured in accordance with Reynolds' specifications in effect on the date of manufacture. These specifications are available upon request. This Warranty does not cover test data, or any defects, damages or other harms caused to any extent or in any way by failure to follow applicable Reynolds instructions, if any, or abuse /misuse of the product.

We believe the information included on this Spec Sheet to be correct, to the best of our knowledge. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that tests be made in a laboratory or plant to determine if this product meets all of your requirements. It is the responsibility of the buyer/user to determine the suitability of this product for his/her application/requirements.

Any claim made or action commenced by purchaser/end user under Reynolds' limited warranty as set forth herein must be brought within one year from date of shipment from Reynolds to the purchaser. Purchaser agrees that all disputes arising from Reynolds' sale of product to purchaser shall be brought, if at all, in and before a court located in the state of South Carolina, to the exclusion of the courts of any other state.

For any valid claim presented under the limited warranty, Reynolds will replace the product, or, at its option, refund the purchase price. This replacement/refund resolution is the purchaser's sole and exclusive remedy against Reynolds. The purchaser agrees that no other resolution (including but not limited to lost profits, lost sales, injury to person or property or any other incidental or consequential loss) shall be available to purchaser for claims arising out of any use of the product regardless of the legal theory (contract, tort or other). In no event will Reynolds be obligated to pay damages to purchaser in any amount exceeding the price that the purchaser paid for the product.

DISCLAIMER - The warranty, as stated above, supersedes all other warranties, express or implied. The Reynolds Company expressly disclaims any other warranties, including warranties of merchantability and fitness for a particular purpose. Reynolds Company's acceptance of purchaser's order for this product is expressly conditional on purchaser's assent to terms and conditions set forth herein. Regardless of whether The Reynolds Company