

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION **PRODUCT IDENTIFIER** SafeTSorb CHEMICAL NAME Montmorillonite Clay, Calcined CHEMICAL FAMILY Clay MATERIAL USE **Oil Absorbent RESTRICTION ON USE** None Known MANUFACTURER EP Minerals, LLC., 9785 Gateway Dr., Reno, NV 89521 **TELEPHONE NO.** (775) 824 7600 (Monday - Friday 8:00 am PST - 5:00 pm PST) EMERGENCY TELEPHONE NO. (775) 824 7600 (Monday - Friday 8:00 am PST - 5:00 pm PST) SDS DATE OF PREPARATION November 27, 2017

SECTION 2: HAZARDS IDENTIFICATION

OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1
HAZARDS NOT OTHERWISE CLASSIFIED	None
LABEL ELEMENTS	DANGER May cause cancer by inhalation. Causes damage to lungs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear eye protection. If exposed or concerned: Get medical advice. Dispose of contents in accordance with local, state and federal regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS
Montmorillonite Clay, Calcined (contains 10-15% Crystalline Silica - Quartz)	100%	70892-59-0 14808-60-7

SECTION 4: FIRST AID MEASURES

EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
SKIN	Use moisture renewing lotions if dryness occurs.
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.
INHALATION	Remove to fresh air. Blow nose to evacuate dust.
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.

MATERIAL NAME					Page 2 of 4
SECTION 5: FIRE FIGHT					
	1		sombustible		
SPECIFIC HAZARDS ARISING	Not applicable, the material is not combustible.				
FROM THE CHEMICAL SPECIAL PROTECTIVE	Not applicable, the material is not combustible.				
EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.				
SECTION 6: ACCIDENT	AL REL	EASE MEASUR	ES		
PERSONAL PRECAUTIONS		If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.			
ENVIRONMENTAL PRECAUTIONS	This mate	erial is not a significant en	vironmental concern.		
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum o	Vacuum clean spillage or wet sweep. Avoid creating airborne dust. Place in a container for use or disposal.			
SECTION 7: HANDLING	AND S	TORAGE			
PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Repair or dispose of broken bags. Observe all label precautions and warnings. Flammable or hazardous substances may retain such characteristics after absorption. Care should be taken to store and dispose of waste material in accordance with instructions of manufacturer of substance absorbed and applicable laws. Do not use with hydrofluoric acid or concentrated caustic solutions.				
CONDITIONS FOR SAFE	Store in a dry place to maintain packaging integrity and product quality. Store product separately from feed, food, pesticides and fertilizers so that cross contaminations does not occur. Do not store near hydrofluoric acid or concentrated caustic solutions.				
STORAGE			oss contaminations do		
SECTION 8: EXPOSURE	concentra	ated caustic solutions.			
	concentra	ated caustic solutions. ROLS / PERSON Note: Processing of sorp	NAL PROTEC		
SECTION 8: EXPOSURE	concentra	ated caustic solutions. ROLS / PERSO	NAL PROTEC	TION	
SECTION 8: EXPOSURE EXPOSURE GUIDELINES:	CONCENT	ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate	NAL PROTEC tive clays is not cover ed with that standard.	TION red by the OSHA Silica Standard	(29CFR1910.1053) and
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa	CONCENT	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust	(29CFR1910.1053) and
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified)	CONCENT	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None Established	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2	(29CFR1910.1053) and NIOSH REL None Established
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified)	CONCENTRA CONT rticulates	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust <u>10 mg/m³</u> % SiO ₂ +2 Respirable dust aral or local exhaust ventil	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None Established 0.025 mg/ m ³ Respirable dust	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust $\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ total dust $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$	(29CFR1910.1053) and NIOSH REL None Established 0.05 mg/ m ³ Respirable dust
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified) Crystalline Silica (Quartz)	CONCENTRA CONT rticulates	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust <u>10 mg/m³</u> % SiO ₂ +2 Respirable dust aral or local exhaust ventil	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None Established 0.025 mg/ m ³ Respirable dust	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust $\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ total dust $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ Respirable dust vithin recommended exposure lim	(29CFR1910.1053) and NIOSH REL None Established 0.05 mg/ m ³ Respirable dust
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified) Crystalline Silica (Quartz) ENGINEERING CONTROLS PERSONAL PROTECTIVE	Concentra CONT rticulates	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust <u>10 mg/m³</u> % SiO ₂ +2 Respirable dust aral or local exhaust ventil	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None Established 0.025 mg/ m ³ Respirable dust	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust $\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ total dust $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ Respirable dust vithin recommended exposure lim	(29CFR1910.1053) and NIOSH REL None Established 0.05 mg/ m ³ Respirable dust
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified) Crystalline Silica (Quartz) ENGINEERING CONTROLS PERSONAL PROTECTIVE EQUIPMENT:	Concentra CONT rticulates Use gene publicatio Goggles t	Ated caustic solutions. ROLS / PERSON Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust <u>10 mg/m³</u> % SiO ₂ +2 Respirable dust eral or local exhaust ventil on "Industrial Ventilation" of	NAL PROTEC tive clays is not cover ad with that standard. ACGIH TLV None Established 0.025 mg/ m ³ Respirable dust	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust $\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ total dust $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ Respirable dust vithin recommended exposure lim	(29CFR1910.1053) and NIOSH REL None Established 0.05 mg/ m ³ Respirable dust
SECTION 8: EXPOSURE EXPOSURE GUIDELINES: Component Montmorillonite Clay, Calcined (as Pa not otherwise classified) Crystalline Silica (Quartz) ENGINEERING CONTROLS PERSONAL PROTECTIVE EQUIPMENT: EYE / FACE PROTECTION	Concentra CONT CONT CONT CONT CONT CONT CONT CONT	Ated caustic solutions. ROLS / PERSOI Note: Processing of sorp the OSHA PEL associate OSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust <u>30 mg/m³</u> % SiO ₂ +2 total dust <u>10 mg/m³</u> % SiO ₂ +2 Respirable dust eral or local exhaust ventil or "Industrial Ventilation" or to protect from dust al equipment is needed. fors fitted with filters certifie If the dust concentration i ask respirator with a N95 (10) times and less than file ecommended. If dust conc a power air-purifying (pos	ACGIH TLV ACGIH TLV None Established 0.025 mg/ m ³ Respirable dust ation to control dust v or similar publications ed to standard 42CFR s less than ten (10) ti dust filter or a single fty (50) times the PEL iccentration is greater itive pressure) respira es the PEL use a typ	TION red by the OSHA Silica Standard MSHA PEL 5 mg/m ³ respirable dust 15 mg/m ³ total dust $\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ total dust $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2+2}$ Respirable dust vithin recommended exposure lim	(29CFR1910.1053) and NIOSH REL None Established 0.05 mg/ m ³ Respirable dust its. Refer to ACGIH orn when dust is mit (PEL) use a quarter concentration is greater with replaceable N95 undred (200) times the If dust concentration is

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE, COLOR	Tan to gray	ODOR	Odorless
PHYSICAL STATE	Solid	ODOR THRESHOLD	Not applicable
VAPOR PRESSURE	Not applicable	VAPOR DENSITY	Not applicable
BOILING POINT	Not applicable	MELTING POINT	Unknown
FLASH POINT	Not applicable	pH (10% SUSPENSION)	Unknown
FLAMMABILITY LIMITS	Not applicable	EVAPORATION RATE	Not applicable
DECOMPOSITION TEMPERATURE	Unknown	SPEC. GRAVITY / RELATIVE DENSITY	2.2
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT - n- OCTANOL/WATER	Not applicable
FLAMMABILITY (solid/gas)	Not applicable	SOLUBILITY - WATER	< 1.0%
		VISCOSITY	Not applicable

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	Material is not reactive.
CHEMICAL STABILITY	Material is stable.
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.
CONDITIONS TO AVOID	Not applicable
INCOMPATIBLE MATERIALS	Unsaturated organic compounds, such as turpentine and vegetable oil, hydrofluoric acid and concentrated caustic solutions may react violently with the product.
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

POTENTIAL REALTH EFFECTS	
Likely Routes of Exposure	See below
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.
INGESTION	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.
CHRONIC EFFECTS	This product contains naturally occurring crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.
CARCINOGENICITY	This natural product is composed predominantly of clay, but contains some crystalline silica. Respirable crystalline silica (quartz) is classified by IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.
NTP	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
IARC	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
NUMERICAL MEASURES OF TOXICITY	No data available

MATERIAL NAME	SafeT	Sorb		Page 4 of 4
CORROSIVENESS, SENSITIZATION, IRRITANCY		Not applicable		
REPRODUCTIVE TOXICITY		Not available		
TERATOGENICITY, MUTAGENICITY		Not available		
SECTION 12: ECOL	OGIC	AL INFORMATION		
ECOTOXICITY:		No toxicity is expected		
PERSISTENCE AND DEGRADABILITY		Non-biodegradable, inert.		
BIOACCUMULATIVE POTENT	IAL	AL Little potential for bioaccumulation		
MOBILITY IN SOIL		No mobility		
OTHER ADVERSE EFFECTS		None known		
SECTION 13: DISPO	SAL	CONSIDERATIONS		
WASTE DISPOSAL		material as supplied becomes a waste, use solid waste disp . Not considered a hazardous waste under RCRA (40CFF		ions or in slurry to
PACKAGING DISPOSAL	Dispo operat	se of in accordance with applicable laws and regulations, ty ions.	pically solid waste disposal common	to landfill type
SECTION 14: TRANS	SPOF	RT INFORMATION		
BASIC SHIPPING INFORMATION	ON	DOT shipping classification 55 (no restrictions). Technical I	name is "Calcined Clay".	
ADDITIONAL INFORMATION		No special requirements or placarding necessary.		
SECTION 15: REGU	LATC	DRY INFORMATION		
U.S. FEDERAL:				
TSCA	Montn	norillonite and Quartz appear on the EPA TSCA inventory li	st.	
CERCLA	Montn Respo	norillonite is not classified as a hazardous substance under onse Compensation and Liability Act (CERCLA), 40 CFR 30	regulations of the Comprehensive E 2.	nvironmental
SARA TITLE III	Not lis	Not listed.		
California Proposition 65:	cause	RNING: This product can expose you to crystalline silica, v cancer. For more information go to www.P65Warnings.ca.		rnia to
SECTION 16: OTHEI	R INF	ORMATION		
			0* Health	
		Yest 4-Extreme 3-High 3-High 2-Moderate Sight	0 Flammability	
		A Construction of the second s	0 Reactivity	
			E Protective Equipment	
ORIGINAL ISSUE DATE	Janua	ry 14, 2014		
REVISION DATE		nber 27, 2017		
REVISION NO.	3			
	Ĭ			

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.