

 Close this window

SDS

**Common Name:** LU103 LQ RUST BREAKER HEAVY DUTY RUST PENETRANT**Manufacturer:** SPRAYON PRODUCTS GROUP**SDS Revision Date:** 11/28/2019**SDS Format:** GHS-US**Item Number(s):** 4GUM6**Manufacturer Model Number(s):**

## SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1. IDENTIFICATION](#)[SECTION 2. HAZARDS IDENTIFICATION](#)[SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS](#)[SECTION 4. FIRST AID MEASURES](#)[SECTION 5. FIRE-FIGHTING MEASURES](#)[SECTION 6. ACCIDENTAL RELEASE MEASURES](#)[SECTION 7. HANDLING AND STORAGE](#)[SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)[SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES](#)[SECTION 10. STABILITY AND REACTIVITY](#)[SECTION 11. TOXICOLOGICAL INFORMATION](#)[SECTION 12. ECOLOGICAL INFORMATION](#)[SECTION 13. DISPOSAL CONSIDERATIONS](#)[SECTION 14. TRANSPORT INFORMATION](#)[SECTION 15. REGULATORY INFORMATION](#)[SECTION 16. OTHER INFORMATION](#)

SAFETY DATA SHEET

SC0103LQ0

## SECTION 1. IDENTIFICATION



PRODUCT NAME: LU(TM)103 LQ RUST BREAKER(R\*) HEAVY DUTY RUST PENETRANT

PRODUCT CODE: SC0103LQ0

OTHER MEANS OF IDENTIFICATION: NOT AVAILABLE.

PRODUCT TYPE: LIQUID.

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: PAINT OR PAINT RELATED MATERIAL.

MANUFACTURER:  
SPRAYON PRODUCTS GROUP  
101 W. PROSPECT AVENUE,  
CLEVELAND, OHIO 44115

EMERGENCY TELEPHONE NUMBER OF THE COMPANY:

US / CANADA: (800) 424-9300

MEXICO:

SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 HOURS / 365 DAYS A YEAR

PRODUCT INFORMATION TELEPHONE NUMBER:

US / CANADA: (800) 247-3266

MEXICO: NOT AVAILABLE

REGULATORY INFORMATION TELEPHONE NUMBER:

US / CANADA: (216) 566-2902

MEXICO: NOT AVAILABLE

TRANSPORTATION EMERGENCY TELEPHONE NUMBER:

US / CANADA: (800) 424-9300

MEXICO:

SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 HOURS / 365 DAYS A YEAR

## SECTION 2. HAZARDS IDENTIFICATION



OSHA/HCS STATUS:

THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

FLAMMABLE LIQUIDS: CATEGORY 4

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (RESPIRATORY TRACT IRRITATION): CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS): CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): CATEGORY 2

ASPIRATION HAZARD: CATEGORY 1

PERCENTAGE OF THE MIXTURE CONSISTING OF INGREDIENT(S) OF UNKNOWN ACUTE ORAL TOXICITY: 84.5%

PERCENTAGE OF THE MIXTURE CONSISTING OF INGREDIENT(S) OF UNKNOWN ACUTE DERMAL TOXICITY: 84.5%

PERCENTAGE OF THE MIXTURE CONSISTING OF INGREDIENT(S) OF UNKNOWN ACUTE INHALATION TOXICITY: 86.1%

GHS LABEL ELEMENTS:

HAZARD PICTOGRAMS:

HEALTH HAZARD

EXCLAMATION MARK

SIGNAL WORD: DANGER

HAZARD STATEMENTS:

COMBUSTIBLE LIQUID.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

MAY CAUSE RESPIRATORY IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

**PRECAUTIONARY STATEMENTS:****PREVENTION:**

WEAR PROTECTIVE GLOVES. WEAR EYE OR FACE PROTECTION. KEEP AWAY FROM FLAMES AND HOT SURFACES. - NO SMOKING. USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. DO NOT BREATHE VAPOR.

**RESPONSE:** GET MEDICAL ATTENTION IF YOU FEEL UNWELL.

**IF INHALED:**

REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL.

**IF SWALLOWED:**

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. DO NOT INDUCE VOMITING.

**STORAGE:** STORE LOCKED UP. STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

**DISPOSAL:**

DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH ALL LOCAL, REGIONAL, NATIONAL AND INTERNATIONAL REGULATIONS.

**SUPPLEMENTAL LABEL ELEMENTS:**

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. CONTAINS SOLVENTS WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. FOR INDUSTRIAL USE ONLY.

PLEASE REFER TO THE SDS FOR ADDITIONAL INFORMATION. KEEP OUT OF REACH OF CHILDREN. DO NOT TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE.

**HAZARDS NOT OTHERWISE CLASSIFIED:** NONE KNOWN.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**SUBSTANCE/MIXTURE:** MIXTURE

**OTHER MEANS OF IDENTIFICATION:** NOT AVAILABLE.

**CAS NUMBER/OTHER IDENTIFIERS:**

INGREDIENT NAME	% BY WEIGHT	CAS NUMBER
ALIPHATIC SOLVENT	>/=75 - </=90	64742-47-8
HEAVY PARAFFINIC OIL	>/=10 - </=25	64742-65-0
CALCIUM DINONYLNAPHTHALENE SULFONATE	>/=3	57855-77-3

ANY CONCENTRATION SHOWN AS A RANGE IS TO PROTECT CONFIDENTIALITY OR IS DUE TO BATCH VARIATION.

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AS HAZARDOUS TO HEALTH AND HENCE REQUIRE REPORTING IN THIS SECTION.

OCCUPATIONAL EXPOSURE LIMITS, IF AVAILABLE, ARE LISTED IN SECTION 8.

**SECTION 4. FIRST AID MEASURES**

**DESCRIPTION OF NECESSARY FIRST AID MEASURES:**

## EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, OCCASIONALLY LIFTING THE UPPER AND LOWER EYELIDS. CHECK FOR AND REMOVE ANY CONTACT LENSES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION FOLLOWING EXPOSURE OR IF FEELING UNWELL.

## INHALATION:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IF NOT BREATHING, IF BREATHING IS IRREGULAR OR IF RESPIRATORY ARREST OCCURS, PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN BY TRAINED PERSONNEL. IT MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH RESUSCITATION. GET MEDICAL ATTENTION. IF NECESSARY, CALL A POISON CENTER OR PHYSICIAN. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

## SKIN CONTACT:

FLUSH CONTAMINATED SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION FOLLOWING EXPOSURE OR IF FEELING UNWELL. WASH CLOTHING BEFORE REUSE. CLEAN SHOES THOROUGHLY BEFORE REUSE.

## INGESTION:

GET MEDICAL ATTENTION IMMEDIATELY. CALL A POISON CENTER OR PHYSICIAN. WASH OUT MOUTH WITH WATER. REMOVE DENTURES IF ANY. REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF MATERIAL HAS BEEN SWALLOWED AND THE EXPOSED PERSON IS CONSCIOUS, GIVE SMALL QUANTITIES OF WATER TO DRINK. STOP IF THE EXPOSED PERSON FEELS SICK AS VOMITING MAY BE DANGEROUS. ASPIRATION HAZARD IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. DO NOT INDUCE VOMITING. IF VOMITING OCCURS, THE HEAD SHOULD BE KEPT LOW SO THAT VOMIT DOES NOT ENTER THE LUNGS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

## MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

## POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

## INHALATION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.

SKIN CONTACT: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

## INGESTION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

## OVER-EXPOSURE SIGNS/SYMPTOMS:

EYE CONTACT: NO SPECIFIC DATA.

## INHALATION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

RESPIRATORY TRACT IRRITATION

COUGHING

NAUSEA OR VOMITING

HEADACHE

DROWSINESS/FATIGUE

DIZZINESS/VERTIGO

UNCONSCIOUSNESS

SKIN CONTACT: NO SPECIFIC DATA.

INGESTION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING: NAUSEA OR VOMITING

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

NOTES TO PHYSICIAN:

TREAT SYMPTOMATICALLY. CONTACT POISON TREATMENT SPECIALIST IMMEDIATELY IF LARGE QUANTITIES HAVE BEEN INGESTED OR INHALED.

SPECIFIC TREATMENTS: NO SPECIFIC TREATMENT.

PROTECTION OF FIRST-AIDERS:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IT MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH RESUSCITATION.

SEE TOXICOLOGICAL INFORMATION (SECTION 11)

## SECTION 5. FIRE-FIGHTING MEASURES



EXTINGUISHING MEDIA:

SUITABLE EXTINGUISHING MEDIA:

USE DRY CHEMICAL, CO2, WATER SPRAY (FOG) OR FOAM.

UNSUITABLE EXTINGUISHING MEDIA: DO NOT USE WATER JET.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

COMBUSTIBLE LIQUID. RUNOFF TO SEWER MAY CREATE FIRE OR EXPLOSION HAZARD. IN A FIRE OR IF HEATED, A PRESSURE INCREASE WILL OCCUR AND THE CONTAINER MAY BURST, WITH THE RISK OF A SUBSEQUENT EXPLOSION.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

DECOMPOSITION PRODUCTS MAY INCLUDE THE FOLLOWING MATERIALS:

CARBON DIOXIDE

CARBON MONOXIDE

SULFUR OXIDES

METAL OXIDE/OXIDES

SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:

PROMPTLY ISOLATE THE SCENE BY REMOVING ALL PERSONS FROM THE VICINITY OF THE INCIDENT IF THERE IS A FIRE. NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. MOVE CONTAINERS FROM FIRE AREA IF THIS CAN BE DONE WITHOUT RISK. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:

FIRE-FIGHTERS SHOULD WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH A FULL FACE-PIECE OPERATED IN POSITIVE PRESSURE MODE.

## SECTION 6. ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

FOR NON-EMERGENCY PERSONNEL:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE

TRAINING. EVACUATE SURROUNDING AREAS. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. DO NOT TOUCH OR WALK THROUGH SPILLED MATERIAL. SHUT OFF ALL IGNITION SOURCES. NO FLARES, SMOKING OR FLAMES IN HAZARD AREA. AVOID BREATHING VAPOR OR MIST. PROVIDE ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

FOR EMERGENCY RESPONDERS:

IF SPECIALIZED CLOTHING IS REQUIRED TO DEAL WITH THE SPILLAGE, TAKE NOTE OF ANY INFORMATION IN SECTION 8 ON SUITABLE AND UNSUITABLE MATERIALS. SEE ALSO THE INFORMATION IN "FOR NON-EMERGENCY PERSONNEL".

ENVIRONMENTAL PRECAUTIONS:

AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS AND SEWERS. INFORM THE RELEVANT AUTHORITIES IF THE PRODUCT HAS CAUSED ENVIRONMENTAL POLLUTION (SEWERS, WATERWAYS, SOIL OR AIR).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

SMALL SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. DILUTE WITH WATER AND MOP UP IF WATER-SOLUBLE. ALTERNATIVELY, OR IF WATER-INSOLUBLE, ABSORB WITH AN INERT DRY MATERIAL AND PLACE IN AN APPROPRIATE WASTE DISPOSAL CONTAINER. DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR.

LARGE SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. APPROACH RELEASE FROM UPWIND. PREVENT ENTRY INTO SEWERS, WATER COURSES, BASEMENTS OR CONFINED AREAS. WASH SPILLAGES INTO AN EFFLUENT TREATMENT PLANT OR PROCEED AS FOLLOWS. CONTAIN AND COLLECT SPILLAGE WITH NON-COMBUSTIBLE, ABSORBENT MATERIAL E.G. SAND, EARTH, VERMICULITE OR DIATOMACEOUS EARTH AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR. CONTAMINATED ABSORBENT MATERIAL MAY POSE THE SAME HAZARD AS THE SPILLED PRODUCT.

NOTE:

SEE SECTION 1 FOR EMERGENCY CONTACT INFORMATION AND SECTION 13 FOR WASTE DISPOSAL.

## SECTION 7. HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING:

PROTECTIVE MEASURES:

PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (SEE SECTION 8). DO NOT BREATHE VAPOR OR MIST. DO NOT SWALLOW. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. DO NOT ENTER STORAGE AREAS AND CONFINED SPACES UNLESS ADEQUATELY VENTILATED. KEEP IN THE ORIGINAL CONTAINER OR AN APPROVED ALTERNATIVE MADE FROM A COMPATIBLE MATERIAL, KEPT TIGHTLY CLOSED WHEN NOT IN USE. STORE AND USE AWAY FROM HEAT, SPARKS, OPEN FLAME OR ANY OTHER IGNITION SOURCE. USE EXPLOSION-PROOF ELECTRICAL (VENTILATING, LIGHTING AND MATERIAL HANDLING) EQUIPMENT. USE ONLY NON-SPARKING TOOLS. EMPTY CONTAINERS RETAIN PRODUCT RESIDUE AND CAN BE HAZARDOUS. DO NOT REUSE CONTAINER.

ADVICE ON GENERAL OCCUPATIONAL HYGIENE:

EATING, DRINKING AND SMOKING SHOULD BE PROHIBITED IN AREAS WHERE THIS MATERIAL IS HANDLED, STORED AND PROCESSED. WORKERS SHOULD WASH HANDS AND FACE BEFORE EATING, DRINKING AND SMOKING. REMOVE CONTAMINATED CLOTHING AND PROTECTIVE EQUIPMENT BEFORE ENTERING EATING AREAS. SEE ALSO SECTION 8 FOR ADDITIONAL INFORMATION ON HYGIENE MEASURES.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:  
 STORE IN ACCORDANCE WITH LOCAL REGULATIONS. STORE IN A SEGREGATED AND APPROVED AREA. STORE IN ORIGINAL CONTAINER PROTECTED FROM DIRECT SUNLIGHT IN A DRY, COOL AND WELL-VENTILATED AREA, AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10) AND FOOD AND DRINK. STORE LOCKED UP. ELIMINATE ALL IGNITION SOURCES. SEPARATE FROM OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED AND SEALED UNTIL READY FOR USE. CONTAINERS THAT HAVE BEEN OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. DO NOT STORE IN UNLABELED CONTAINERS. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION. SEE SECTION 10 FOR INCOMPATIBLE MATERIALS BEFORE HANDLING OR USE.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



### CONTROL PARAMETERS:

#### OCCUPATIONAL EXPOSURE LIMITS (OSHA UNITED STATES):

INGREDIENT NAME	CAS #	EXPOSURE LIMITS
ALIPHATIC SOLVENT	64742-47-8	ACGIH TLV (UNITED STATES, 3/2019). ABSORBED THROUGH SKIN. TWA: 200 MG/M3, (AS TOTAL HYDROCARBON VAPOR) 8 HOURS.
HEAVY PARAFFINIC OIL	64742-65-0	OSHA PEL (UNITED STATES, 5/2018). TWA: 5 MG/M3 8 HOURS.  ACGIH TLV (UNITED STATES, 3/2019). TWA: 5 MG/M3 8 HOURS. FORM: INHALABLE FRACTION  NIOSH REL (UNITED STATES, 10/2016). TWA: 5 MG/M3 10 HOURS. FORM: MIST STEL: 10 MG/M3 15 MINUTES. FORM: MIST
CALCIUM DINONYLNAPHTHALENE SULFONATE	57855-77-3	NONE.

#### OCCUPATIONAL EXPOSURE LIMITS (CANADA):

INGREDIENT NAME	CAS #	EXPOSURE LIMITS
PETROLEUM REFINING,   HYDROTREATED LIGHT   DISTILLATE	64742-47-8	CA BRITISH COLUMBIA PROVINCIAL (CANADA, 5/2019). ABSORBED THROUGH SKIN. TWA: 200 MG/M3, (AS TOTAL HYDROCARBON VAPOUR) 8 HOURS.  CA ALBERTA PROVINCIAL (CANADA, 6/2018). ABSORBED THROUGH SKIN. 8 HRS OEL: 200 MG/M3, (AS TOTAL HYDROCARBON VAPOUR) 8 HOURS.  CA ONTARIO PROVINCIAL (CANADA, 1/2018). ABSORBED THROUGH SKIN. TWA: 200 MG/M3, (AS TOTAL HYDROCARBON VAPOUR) 8 HOURS.

HEAVY PARAFFINIC OIL 64742-65-0 CA ALBERTA PROVINCIAL (CANADA, 6/2018).  
 8 HRS OEL: 5 MG/M3 8 HOURS.  
 FORM: MIST  
 15 MIN OEL: 10 MG/M3 15 MINUTES.  
 FORM: MIST

CA QUEBEC PROVINCIAL (CANADA, 1/2014).  
 TWA EV: 5 MG/M3 8 HOURS.  
 FORM: MIST  
 STEV: 10 MG/M3 15 MINUTES.  
 FORM: MIST

OCCUPATIONAL EXPOSURE LIMITS (MEXICO):

	CAS #	EXPOSURE LIMITS
ALIPHATIC SOLVENT	64742-47-8	ACGIH TLV (UNITED STATES, 3/2019). ABSORBED THROUGH SKIN. TWA: 200 MG/M3, (AS TOTAL HYDROCARBON VAPOR) 8 HOURS.
HEAVY PARAFFINIC OIL	64742-65-0	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 5 MG/M3 8 HOURS. FORM: MIST

APPROPRIATE ENGINEERING CONTROLS:

USE ONLY WITH ADEQUATE VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP WORKER EXPOSURE TO AIRBORNE CONTAMINANTS BELOW ANY RECOMMENDED OR STATUTORY LIMITS. THE ENGINEERING CONTROLS ALSO NEED TO KEEP GAS, VAPOR OR DUST CONCENTRATIONS BELOW ANY LOWER EXPLOSIVE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

ENVIRONMENTAL EXPOSURE CONTROLS:

EMISSIONS FROM VENTILATION OR WORK PROCESS EQUIPMENT SHOULD BE CHECKED TO ENSURE THEY COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION LEGISLATION. IN SOME CASES, FUME SCRUBBERS, FILTERS OR ENGINEERING MODIFICATIONS TO THE PROCESS EQUIPMENT WILL BE NECESSARY TO REDUCE EMISSIONS TO ACCEPTABLE LEVELS.

INDIVIDUAL PROTECTION MEASURES:

HYGIENE MEASURES:

WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING, SMOKING AND USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. APPROPRIATE TECHNIQUES SHOULD BE USED TO REMOVE POTENTIALLY CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

EYE/FACE PROTECTION:

SAFETY EYEWEAR COMPLYING WITH AN APPROVED STANDARD SHOULD BE USED WHEN A RISK ASSESSMENT INDICATES THIS IS NECESSARY TO AVOID EXPOSURE TO LIQUID SPLASHES, MISTS, GASES OR DUSTS. IF CONTACT IS POSSIBLE, THE FOLLOWING PROTECTION SHOULD BE WORN, UNLESS THE ASSESSMENT INDICATES A HIGHER DEGREE OF PROTECTION: SAFETY GLASSES WITH SIDE-SHIELDS.

SKIN PROTECTION:

HAND PROTECTION:

CHEMICAL-RESISTANT, IMPERVIOUS GLOVES COMPLYING WITH AN APPROVED STANDARD SHOULD BE WORN AT ALL TIMES WHEN HANDLING CHEMICAL PRODUCTS IF A RISK ASSESSMENT INDICATES THIS IS NECESSARY. CONSIDERING THE PARAMETERS SPECIFIED BY THE GLOVE MANUFACTURER, CHECK DURING USE THAT THE GLOVES ARE STILL RETAINING THEIR PROTECTIVE PROPERTIES. IT SHOULD BE NOTED THAT THE TIME TO BREAKTHROUGH FOR ANY GLOVE MATERIAL MAY BE DIFFERENT FOR DIFFERENT



GLOVE MANUFACTURERS. IN THE CASE OF MIXTURES, CONSISTING OF SEVERAL SUBSTANCES, THE PROTECTION TIME OF THE GLOVES CANNOT BE ACCURATELY ESTIMATED.

**BODY PROTECTION:**

PERSONAL PROTECTIVE EQUIPMENT FOR THE BODY SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT.

**OTHER SKIN PROTECTION:**

APPROPRIATE FOOTWEAR AND ANY ADDITIONAL SKIN PROTECTION MEASURES SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT.

**RESPIRATORY PROTECTION:**

BASED ON THE HAZARD AND POTENTIAL FOR EXPOSURE, SELECT A RESPIRATOR THAT MEETS THE APPROPRIATE STANDARD OR CERTIFICATION. RESPIRATORS MUST BE USED ACCORDING TO A RESPIRATORY PROTECTION PROGRAM TO ENSURE PROPER FITTING, TRAINING, AND OTHER IMPORTANT ASPECTS OF USE.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE:**

PHYSICAL STATE: LIQUID.

COLOR: NOT AVAILABLE.

ODOR: NOT AVAILABLE.

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

MELTING POINT/FREEZING POINT: NOT AVAILABLE.

BOILING POINT/BOILING RANGE: 216 DEG. C (420.8 DEG. F)

**FLASH POINT:**

CLOSED CUP: 93 DEG. C (199.4 DEG. F) [PENSKY-MARTENS CLOSED CUP]

EVAPORATION RATE: 0.192 (BUTYL ACETATE = 1)

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE.

**LOWER AND UPPER EXPLOSIVE (FLAMMABLE) LIMITS:**

LOWER: 0.7%

UPPER: 6%

VAPOR PRESSURE: 0.00093 KPA (0.007 MM HG) [AT 20 DEG. C]

VAPOR DENSITY: NOT AVAILABLE.

RELATIVE DENSITY: 0.79

SOLUBILITY: NOT AVAILABLE.

PARTITION COEFFICIENT N-OCTANOL/WATER: NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: NOT AVAILABLE.

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

**VISCOSITY:**

KINEMATIC (40 DEG. C (104 DEG. F)): <0.205 CM<sup>2</sup>/S (<20.5 CST)

MOLECULAR WEIGHT: NOT APPLICABLE.

AEROSOL PRODUCT:

HEAT OF COMBUSTION: 40.038 KJ/G

## SECTION 10. STABILITY AND REACTIVITY



REACTIVITY:

NO SPECIFIC TEST DATA RELATED TO REACTIVITY AVAILABLE FOR THIS PRODUCT OR ITS INGREDIENTS.

CHEMICAL STABILITY: THE PRODUCT IS STABLE.

POSSIBILITY OF HAZARDOUS REACTIONS:

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS REACTIONS WILL NOT OCCUR.

CONDITIONS TO AVOID:

AVOID ALL POSSIBLE SOURCES OF IGNITION (SPARK OR FLAME). DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE CONTAINERS TO HEAT OR SOURCES OF IGNITION.

INCOMPATIBLE MATERIALS:

REACTIVE OR INCOMPATIBLE WITH THE FOLLOWING MATERIALS: OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION PRODUCTS:

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS DECOMPOSITION PRODUCTS SHOULD NOT BE PRODUCED.

## SECTION 11. TOXICOLOGICAL INFORMATION



INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
HEAVY PARAFFINIC OIL	LD50 DERMAL	RABBIT	>5000 MG/KG	
	LD50 ORAL	RAT	>5000 MG/KG	
CALCIUM	LD50 DERMAL	RABBIT	>20 G/KG	
DINONYLNAPHTHALENE SULFONATE	LD50 ORAL	RAT	>5000 MG/KG	

IRRITATION/CORROSION:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
CALCIUM	SKIN - MODERATE IRRITANT	RABBIT		0.5 ML	
DINONYLNAPHTHALENE					
SULFONATE					

SENSITIZATION: NOT AVAILABLE.

MUTAGENICITY: NOT AVAILABLE.

CARCINOGENICITY: NOT AVAILABLE.

REPRODUCTIVE TOXICITY: NOT AVAILABLE.

TERATOGENICITY: NOT AVAILABLE.

## SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) :

NAME	CATEGORY	ROUTE OF EXPOSURE	TARGET ORGANS
ALIPHATIC SOLVENT	CATEGORY 3	NOT APPLICABLE.	NARCOTIC EFFECTS
	CATEGORY 3	NOT APPLICABLE.	RESPIRATORY TRACT IRRITATION

## SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) :

NAME	CATEGORY	ROUTE OF EXPOSURE	TARGET ORGANS
ALIPHATIC SOLVENT	CATEGORY 2	NOT DETERMINED	NOT DETERMINED

## ASPIRATION HAZARD:

NAME	RESULT
ALIPHATIC SOLVENT	ASPIRATION HAZARD - CATEGORY 1
HEAVY PARAFFINIC OIL	ASPIRATION HAZARD - CATEGORY 1

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE: NOT AVAILABLE.

POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

## INHALATION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.

SKIN CONTACT: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

## INGESTION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

EYE CONTACT: NO SPECIFIC DATA.

## INHALATION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

RESPIRATORY TRACT IRRITATION  
 COUGHING  
 NAUSEA OR VOMITING  
 HEADACHE  
 DROWSINESS/FATIGUE  
 DIZZINESS/VERTIGO  
 UNCONSCIOUSNESS

SKIN CONTACT: NO SPECIFIC DATA.

## INGESTION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING: NAUSEA OR VOMITING

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE:

## SHORT TERM EXPOSURE:

POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.  
 POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

## LONG TERM EXPOSURE:

POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.

POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

POTENTIAL CHRONIC HEALTH EFFECTS: NOT AVAILABLE.

GENERAL: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

CARCINOGENICITY: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

MUTAGENICITY: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

TERATOGENICITY: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

DEVELOPMENTAL EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

FERTILITY EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

## NUMERICAL MEASURES OF TOXICITY:

ACUTE TOXICITY ESTIMATES: NOT AVAILABLE.

**SECTION 12. ECOLOGICAL INFORMATION**

## TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	EXPOSURE
ALIPHATIC SOLVENT	ACUTE LC50: 2200 (MICRO)G/L FRESH WATER	FISH - LEPOMIS MACROCHIRUS	4 DAYS

PERSISTENCE AND DEGRADABILITY: NOT AVAILABLE.

BIOACCUMULATIVE POTENTIAL: NOT AVAILABLE.

## MOBILITY IN SOIL:

SOIL/WATER PARTITION COEFFICIENT (KOC): NOT AVAILABLE.

OTHER ADVERSE EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

**SECTION 13. DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS:

THE GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHEREVER POSSIBLE. DISPOSAL OF THIS PRODUCT, SOLUTIONS AND ANY BY-PRODUCTS SHOULD AT ALL TIMES COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL LEGISLATION AND ANY REGIONAL LOCAL AUTHORITY REQUIREMENTS. DISPOSE OF SURPLUS AND NON-RECYCLABLE PRODUCTS VIA A LICENSED WASTE DISPOSAL CONTRACTOR. WASTE SHOULD NOT BE DISPOSED OF UNTREATED TO THE SEWER UNLESS FULLY COMPLIANT WITH THE REQUIREMENTS OF ALL AUTHORITIES WITH JURISDICTION. WASTE PACKAGING SHOULD BE RECYCLED. INCINERATION OR LANDFILL SHOULD ONLY BE CONSIDERED WHEN RECYCLING IS NOT FEASIBLE. THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY. CARE SHOULD BE TAKEN WHEN HANDLING EMPTIED CONTAINERS THAT HAVE NOT BEEN CLEANED OR RINSED OUT. EMPTY CONTAINERS OR LINERS MAY RETAIN SOME PRODUCT RESIDUES. VAPOR FROM PRODUCT RESIDUES MAY CREATE A HIGHLY FLAMMABLE OR EXPLOSIVE ATMOSPHERE INSIDE THE CONTAINER. DO NOT CUT, WELD OR GRIND USED CONTAINERS UNLESS THEY HAVE BEEN CLEANED THOROUGHLY INTERNALLY. AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS AND SEWERS.

**SECTION 14. TRANSPORT INFORMATION**

	DOT CLASSIFI- CATION	TDG CLASSIFI- CATION	MEXICO CLASSIFI- CATION	IATA	IMDG
UN NUMBER	NOT REGULATED.	NOT REGULATED.	NOT REGULATED.	NOT REGULATED.	NOT REGULATED.

UN PROPER  
SHIPPING NAME

TRANSPORT  
HAZARD  
CLASS (ES)

PACKING  
GROUP

ENVIRONMENTAL HAZARDS	NO.	NO.	NO.	NO.	NO.

ADDITIONAL  
INFORMATION

**SPECIAL PRECAUTIONS FOR USER:**

MULTI-MODAL SHIPPING DESCRIPTIONS ARE PROVIDED FOR INFORMATIONAL PURPOSES AND DO NOT CONSIDER CONTAINER SIZES. THE PRESENCE OF A SHIPPING DESCRIPTION FOR A PARTICULAR MODE OF TRANSPORT (SEA, AIR, ETC.), DOES NOT INDICATE THAT THE PRODUCT IS PACKAGED SUITABLY FOR THAT MODE OF TRANSPORT. ALL PACKAGING MUST BE REVIEWED FOR SUITABILITY PRIOR TO SHIPMENT, AND COMPLIANCE WITH THE APPLICABLE REGULATIONS IS THE SOLE RESPONSIBILITY OF THE PERSON OFFERING THE PRODUCT FOR TRANSPORT. PEOPLE LOADING AND UNLOADING DANGEROUS GOODS MUST BE TRAINED ON ALL OF THE RISKS DERIVING FROM THE SUBSTANCES AND ON ALL ACTIONS IN CASE OF EMERGENCY SITUATIONS.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL AND THE IBC CODE:  
NOT AVAILABLE.

PROPER SHIPPING NAME: NOT AVAILABLE.

SHIP TYPE: NOT AVAILABLE.

POLLUTION CATEGORY: NOT AVAILABLE.

**SECTION 15. REGULATORY INFORMATION****SARA 313:**

SARA 313 (40 CFR 372.45) SUPPLIER NOTIFICATION CAN BE FOUND ON THE ENVIRONMENTAL DATA SHEET.

CALIFORNIA PROP. 65: NOT APPLICABLE.

**INTERNATIONAL REGULATIONS:****INTERNATIONAL LISTS:**

AUSTRALIA INVENTORY (AICS): NOT DETERMINED.  
CHINA INVENTORY (IECSC): NOT DETERMINED.  
JAPAN INVENTORY (ENCS): NOT DETERMINED.  
JAPAN INVENTORY (ISHL): NOT DETERMINED.  
KOREA INVENTORY (KECI): NOT DETERMINED.  
NEW ZEALAND INVENTORY OF CHEMICALS (NZIOC): NOT DETERMINED.  
PHILIPPINES INVENTORY (PICCS): NOT DETERMINED.  
TAIWAN CHEMICAL SUBSTANCES INVENTORY (TCSI): NOT DETERMINED.

THAILAND INVENTORY: NOT DETERMINED.  
 TURKEY INVENTORY: NOT DETERMINED.  
 VIETNAM INVENTORY: NOT DETERMINED.

## SECTION 16. OTHER INFORMATION



HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.):

HEALTH / 2  
 FLAMMABILITY 1  
 PHYSICAL HAZARDS 0

THE CUSTOMER IS RESPONSIBLE FOR DETERMINING THE PPE CODE FOR THIS MATERIAL.  
 FOR MORE INFORMATION ON HMIS(R\*) PERSONAL PROTECTIVE EQUIPMENT (PPE) CODES,  
 CONSULT THE HMIS(R\*) IMPLEMENTATION MANUAL.

### CAUTION:

HMIS(R\*) RATINGS ARE BASED ON A 0-4 RATING SCALE, WITH 0 REPRESENTING  
 MINIMAL HAZARDS OR RISKS, AND 4 REPRESENTING SIGNIFICANT HAZARDS OR RISKS.  
 ALTHOUGH HMIS(R\*) RATINGS AND THE ASSOCIATED LABEL ARE NOT REQUIRED ON SDSS  
 OR PRODUCTS LEAVING A FACILITY UNDER 29 CFR 1910.1200, THE PREPARER MAY  
 CHOOSE TO PROVIDE THEM. HMIS(R\*) RATINGS ARE TO BE USED WITH A FULLY  
 IMPLEMENTED HMIS(R\*) PROGRAM. HMIS(R\*) IS A REGISTERED TRADEMARK AND  
 SERVICE MARK OF THE AMERICAN COATINGS ASSOCIATION, INC.

### PROCEDURE USED TO DERIVE THE CLASSIFICATION:

CLASSIFICATION	JUSTIFICATION
FLAMMABLE LIQUIDS - CATEGORY 4	ON BASIS OF TEST DATA
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (RESPIRATORY TRACT IRRITATION) - CATEGORY 3	CALCULATION METHOD
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS) - CATEGORY 3	CALCULATION METHOD
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - CATEGORY 2	CALCULATION METHOD
ASPIRATION HAZARD - CATEGORY 1	CALCULATION METHOD

### HISTORY:

DATE OF PRINTING: 11/28/2019

DATE OF ISSUE/DATE OF REVISION: 11/28/2019

DATE OF PREVIOUS ISSUE: 8/1/2019

VERSION: 7

### KEY TO ABBREVIATIONS:

ATE: ACUTE TOXICITY ESTIMATE

BCF: BIOCONCENTRATION FACTOR

GHS: GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS

IATA: INTERNATIONAL AIR TRANSPORT ASSOCIATION

IBC: INTERMEDIATE BULK CONTAINER

IMDG: INTERNATIONAL MARITIME DANGEROUS GOODS

LOGPOW: LOGARITHM OF THE OCTANOL/WATER PARTITION COEFFICIENT

MARPOL:

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973  
AS MODIFIED BY THE PROTOCOL OF 1978. ("MARPOL" = MARINE POLLUTION)

N/A: NOT AVAILABLE

SGG: SEGREGATION GROUP

UN: UNITED NATIONS

| INDICATES INFORMATION THAT HAS CHANGED FROM PREVIOUSLY ISSUED VERSION.

NOTICE TO READER:

IT IS RECOMMENDED THAT EACH CUSTOMER OR RECIPIENT OF THIS SAFETY DATA SHEET (SDS) STUDY IT CAREFULLY AND CONSULT RESOURCES, AS NECESSARY OR APPROPRIATE, TO BECOME AWARE OF AND UNDERSTAND THE DATA CONTAINED IN THIS SDS AND ANY HAZARDS ASSOCIATED WITH THE PRODUCT. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE ACCURATE AS OF THE EFFECTIVE DATE HEREIN. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN. THE INFORMATION PRESENTED HERE APPLIES ONLY TO THE PRODUCT AS SHIPPED. THE ADDITION OF ANY MATERIAL CAN CHANGE THE COMPOSITION, HAZARDS AND RISKS OF THE PRODUCT. PRODUCTS SHALL NOT BE REPACKAGED, MODIFIED, OR TINTED EXCEPT AS SPECIFICALLY INSTRUCTED BY THE MANUFACTURER, INCLUDING BUT NOT LIMITED TO THE INCORPORATION OF PRODUCTS NOT SPECIFIED BY THE MANUFACTURER, OR THE USE OR ADDITION OF PRODUCTS IN PROPORTIONS NOT SPECIFIED BY THE MANUFACTURER. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER BETWEEN VARIOUS LOCATIONS AND JURISDICTIONS. THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO ENSURE THAT HIS ACTIVITIES COMPLY WITH ALL COUNTRY, FEDERAL, STATE, PROVINCIAL OR LOCAL LAWS. THE CONDITIONS FOR USE OF THE PRODUCT ARE NOT UNDER THE CONTROL OF THE MANUFACTURER; THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO DETERMINE THE CONDITIONS NECESSARY FOR THE SAFE USE OF THIS PRODUCT. THE CUSTOMER/BUYER/USER SHOULD NOT USE THE PRODUCT FOR ANY PURPOSE OTHER THAN THE PURPOSE SHOWN IN THE APPLICABLE SECTION OF THIS SDS WITHOUT FIRST REFERRING TO THE SUPPLIER AND OBTAINING WRITTEN HANDLING INSTRUCTIONS. DUE TO THE PROLIFERATION OF SOURCES FOR INFORMATION SUCH AS MANUFACTURER-SPECIFIC SDS, THE MANUFACTURER CANNOT BE RESPONSIBLE FOR SDSS OBTAINED FROM ANY OTHER SOURCE.

SHW-85-NA-GHS-US