

DARK TAN IN NYLON LD 10%

Version 1.0 Revision Date: 06/13/2015 MSDS Number: F000001494 Date of last issue: -
Date of first issue: 06/13/2015

SECTION 1. IDENTIFICATION

Product name : DARK TAN IN NYLON LD 10%

Product code : F000001494
000000000000024151

Manufacturer or supplier's details

Company name of supplier : Advanced Color Technologies, LLC
Address : 1727 Kimberly Park Drive
Dalton GA 30720

Emergency telephone number : (CHEMTREC): (800) 424-9300 (CHEMTREC International):
(703) 527-3887 Industrial Health/Spill Emergency: (706) 277-
1300 Danny Welch (ehs@trcc.com)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2B

GHS Label element

Hazard pictograms :



Signal word : Warning

Hazard statements : H320 Causes eye irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:
84.9706 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Chrome antimony titanium buff rutile	68186-90-3	>= 10 - < 20

DARK TAN IN NYLON LD 10%

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	06/13/2015	F000001494	Date of first issue: 06/13/2015

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| If inhaled | : | Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. If symptoms persist, call a physician. |
| In case of skin contact | : | Wash off with soap and water. If symptoms persist, call a physician. Cool skin rapidly with cold water after contact with molten material. |
| In case of eye contact | : | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. |
| If swallowed | : | Do not induce vomiting without medical advice. If conscious, drink plenty of water. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : | None known. |
-

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---|---|--|
| Suitable extinguishing media | : | Foam
Carbon dioxide (CO ₂)
ABC powder
Water mist |
| Specific hazards during fire-fighting | : | Fire will produce dense black smoke containing hazardous combustion products (see section 10). |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : | Use personal protective equipment. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Ventilate the area.
Avoid dust formation.
Use personal protective equipment.
Avoid breathing dust. |
| Environmental precautions | : | Should not be released into the environment. Do not let product enter drains. Prevent further leakage or spillage. Clean contaminated floors and objects thoroughly while observing environmental regulations. |

DARK TAN IN NYLON LD 10%

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	06/13/2015	F000001494	Date of first issue: 06/13/2015

Methods and materials for containment and cleaning up : Sweep up and shovel.
Clean contaminated floors and objects thoroughly while observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use only in area provided with appropriate exhaust ventilation. If formation of dust is observed, equipment has to be switched off, cleaned and serviced. Keep away from heat and sources of ignition.

Advice on safe handling : Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.
Handle with care.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
Store at room temperature in the original container.
Observe label precautions.
Do not store near combustible materials.

Materials to avoid : Keep away from food and drink.
Keep away from tobacco products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Chrome antimony titanium buff rutile	68186-90-3	TWA	0.5 mg/m ³ (antimony)	OSHA Z-1
		TWA	0.5 mg/m ³ (antimony)	ACGIH
		TWA	0.5 mg/m ³ (antimony)	OSHA P0
		TWA	0.5 mg/m ³ (antimony)	NIOSH REL

Engineering measures : Electrostatic precipitation for dust collection.
Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Respiratory protection : Use NIOSH approved respiratory protection.

Hand protection
Material : Impervious gloves

Eye protection : Safety glasses with side-shields

DARK TAN IN NYLON LD 10%

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	06/13/2015	F000001494	Date of first issue: 06/13/2015

Skin and body protection	:	Tightly fitting safety goggles Face-shield
Protective measures	:	Chemical resistant apron Footwear protecting against chemicals Skin should be washed after contact. Change working clothes after each workshift. Avoid contact with skin. When using do not eat or drink. Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hygiene measures	:	Do not smoke. Keep away from food and drink. Avoid contact with skin, eyes and clothing. Change working clothes after each workshift. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	pellets
Colour	:	tan
Odour	:	slight
pH	:	No data available
Melting point/range	:	210 °C
Boiling point/boiling range	:	No data available
Flash point	:	320 - 350 °C
Vapour pressure	:	No data available
Density	:	1,200 kg/m ³
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	Not applicable
Partition coefficient: n-octanol/water	:	No data available
Explosive properties	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Protect from frost.
Incompatible materials	:	Oxidizing agents Strong acids and strong bases

DARK TAN IN NYLON LD 10%

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	06/13/2015	F000001494	Date of first issue: 06/13/2015

Hazardous decomposition products	:	Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), dense black smoke.
----------------------------------	---	--

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity	:	Remarks: This information is not available.
Acute inhalation toxicity	:	Remarks: This information is not available.
Acute dermal toxicity	:	Remarks: This information is not available.

Skin corrosion/irritation**Product:**

Remarks: This information is not available.

Serious eye damage/eye irritation**Product:**

Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: This information is not available.

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish	:	
------------------	---	--

DARK TAN IN NYLON LD 10%

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	06/13/2015	F000001494	Date of first issue: 06/13/2015

Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates :
Remarks: No data available

Toxicity to algae :
Remarks: No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Contaminated packaging : Clean container with water.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulation****Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

National Regulations**SECTION 15. REGULATORY INFORMATION**

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:


Chrome antimony titanium	68186-90-3	15.63 %
buff rutile		

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

DARK TAN IN NYLON LD 10%

Version 1.0 Revision Date: 06/13/2015 MSDS Number: F000001494 Date of last issue: -
Date of first issue: 06/13/2015

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 06/13/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN