

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00328 MST VOC ECONOMY SILICONE 16net10

Material number : 00000000001033570

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers
For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION
Emergency Overview

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | clear, colourless |
| Odour | characteristic |

GHS Classification

 Flammable aerosols : Category 1
 Gases under pressure : Liquefied gas
 Specific target organ toxicity - single exposure : Category 1

GHS Label element

Hazard pictograms :



Signal word : Danger

 Hazard statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H370 Causes damage to organs.

 Precautionary statements : **Prevention:**
 P210 Keep away from heat/sparks/open flames/hot surfaces.
 No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

Potential Health Effects**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical Name | CAS-No. | Concentration [%] |
|---------------------------------------------|------------|-------------------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | >= 30 - < 50 |
| Petroleum Distillates | 64742-96-7 | >= 30 - < 50 |
| propane | 74-98-6 | >= 30 - < 50 |
| butane | 106-97-8 | >= 20 - < 30 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
If on skin, rinse well with water.

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

If on clothes, remove clothes.

- In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------------------------------------------|------------|----------------------------------|---------------------------------------------------|-----------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA | 500 ppm 2,000 mg/m ³ | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m ³ | OSHA P0 |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | OSHA P0 |
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m ³ | NIOSH REL |

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

| | | | | |
|--|--|-----|------------------------|---------|
| | | TWA | 800 ppm 1,900 mg/m3 | OSHA P0 |
|--|--|-----|------------------------|---------|

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Safety glasses
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : clear, colourless
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Boiling point : No data available
- Flash point :
No data available
- Evaporation rate : < 1
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : 0.785 g/cm3
- Solubility(ies)

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

| | |
|----------------------------------------|---------------------|
| Water solubility | : insoluble |
| Solubility in other solvents | : not determined |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : 46.7 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Extremes of temperature and direct sunlight. Heat, flames and sparks. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | : Carbon oxides |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Components:****Distillates (petroleum), hydrotreated light:**

| | |
|---------------------------|----------------------------------------------|
| Acute oral toxicity | : LD50 Rat: > 5,000 mg/kg |
| Acute inhalation toxicity | : LC50 Rat: > 4.6 mg/l Exposure time: 6 h |
| Acute dermal toxicity | : LD50 Rat: > 2,000 mg/kg |

propane:

| | |
|---------------------------|------------------------------------------------|
| Acute inhalation toxicity | : LC50 Mouse: 1,237 mg/l Exposure time: 2 h |
|---------------------------|------------------------------------------------|

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: May irritate eyes.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated light:

Petroleum Distillates:

propane:

butane:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product:**

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

| |
|-----------------------------------------------------------------------|
| Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY |
|-----------------------------------------------------------------------|

| |
|---------------------------------------------------------------------------------------------------|
| Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|---------------------------------------------------------------------------------------------------|

| |
|------------------------------------------------------------------------------------------------------|
| Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|------------------------------------------------------------------------------------------------------|

| |
|----------------------------------------------------------------------------------------------------------|
| Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|----------------------------------------------------------------------------------------------------------|

| |
|--------------------------------------------------------------------------------------------------|
| Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|--------------------------------------------------------------------------------------------------|

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards
Fire Hazard
Sudden Release of Pressure Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

California Prop 65


This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

| | |
|--------------|--------------------------------------------------------|
| TSCA | On TSCA Inventory |
| DSL | All components of this product are on the Canadian DSL |
| AICS | On the inventory, or in compliance with the inventory |
| NZIoC | Not in compliance with the inventory |
| PICCS | On the inventory, or in compliance with the inventory |
| IECSC | On the inventory, or in compliance with the inventory |

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

| | |
|------------------------|----------|
| HEALTH | 3 |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms :



Signal word :

Hazard statements :

Precautionary statements :

Danger:
Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Causes damage to organs.

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Response: IF exposed: Call a POISON CENTER or doctor/physician.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET



A00328 MST VOC ECONOMY SILICONE 16net10

Version 2.0

Revision Date 09/30/2015

Print Date 05/10/2016

| | |
|----------------|------------|
| Version: | 2.0 |
| Revision Date: | 09/30/2015 |
| Print Date: | 05/10/2016 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.